

Product News

PRODUCT BULLETIN # 234

Date: 2/9/07
Subject: Chicago Faucets – HyTronic Less Spout Products
To: All Commercial Customers
From: Patrick Tanzillo, Product Manager, Commercial Products







Chicago Faucets is pleased to announce HyTronic products in less spout configurations that are available for immediate sale. These new offerings expand the HyTronic product line and allow for a broad spectrum of applications specific to your needs.

Product Benefits

- Product Line Expansion
- Standard Body Threads ensure Compatibility with Chicago Faucet Spouts (See Spout Schedule)
- Standard Product Availability and Lead Times
- Compliant to ASME A112.18.1, CSA B125.1 and ADA

New Models Numbers

Product Number	Description	List Price	Image
116.323.21.1	Gooseneck Less Spout, AC, External Mixer	590.95	
116.313.21.1	Gooseneck Less Spout, AC, Internal Mixer	569.00	
116.303.21.1	Gooseneck Less Spout, AC, No Mixer	547.78	
116.423.21.1	Gooseneck Less Spout, DC, External Mixer	563.74	

116.413.21.1	Gooseneck Less Spout, DC, Internal Mixer	541.79	
116.403.21.1	Gooseneck Less Spout, DC, No Mixer	520.57	
116.314.21.1	Wall Mount Less Spout, AC, Internal Mixer	629.05	
116.304.21.1	Wall Mount Less Spout, AC, Single Supply	607.41	
116.414.21.1	Wall Mount Less Spout, DC, Internal Mixer	601.84	
116.404.21.1	Wall Mount Less Spout, DC, Single Supply	580.20	

HyTronic Spout Selection Data

The HyTronic faucet sensor range is preset at the factory for 6" (+/- 1/2") from the center of the spout to the center of the outlet. For optimal performance when using spouts outside of this range, the Commander™ Software must be used to adjust the electronic sensor range setting. In addition, spouts that have excessive heights, such as the non-standard GN2H13JKCP and GN2H17JKCP, are not ideal applications due to excessive height from the distance of the sensor to the spout outlet.

	Spout Types												
	GN1	GN2	GN2H8	GN8	GN10	GN12	HA8	L8	L9	L12	L15	GN2H13	GN2H17
Commander™ Software Change	Yes	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	*NR	*NR

*Not Recommended

Ordering Information

Due to lead-time variances between fittings and components, sales orders placed for HyTronic less spout product should be marked as "Ship Complete" to ensure that spouts are shipped at the same time of the faucet base model.

Warranty

Chicago Faucets' HyTronic products are warranted to be free from defects in material and workmanship for a period of five (5) years from the date of purchase when properly installed and serviced. HyTronic products have a lifetime warranty on the brass body and a one (1) year warranty on the chrome plate.

Promotional / Sales Support Information

The website will be updated with photos, product descriptions and drawings by February 19, 2007

If you have any questions or comments please contact Patrick Tanzillo at 847.803.5000, ext. 226 or pat.tanzillo@chicagofaucets.com .