

**CHICAGO
FAUCETS®**
Geberit Group

EVR Series Touchless Lavatory Faucets

Integrated scald protection with durable touchless convenience



TempShield®
Available with integrated
ASSE 1070 Certified
scald protection.*

EVR Series

A Hard Working Overachiever.

The EVR Series combines the safety and convenience of touchless operation with the durability of a heavy-duty, one-piece cast brass body. Power options and mixing – including integrated ASSE 1070 certified scald protection* – are concealed in a secure, easy to install, compact control box.

Durable Construction


Heavy-duty, one-piece cast brass body with vandal resistant outlet designed to withstand abuse and tampering.

Improved User Experience

Higher and longer spout reach combined with dependable electronics facilitate thorough handwashing.

The **CF Connect** App provides a secure and easy way to adjust and maintain the faucet with a smartphone.

- Hygiene Flush eliminates stagnant water from the plumbing system and removes harmful bacteria
- Six field-adjustable modes for metering, water savings, and detection ranges
- Track Usage



Optional Scald Protection

Available with integral ASSE 1070 certified scald protection* to help prevent scalding.

Cuts installation time over 50%.

Fewer connections eliminate as many as six potential leak points.

Simple and Secure Enclosure

Reduces connections and complexity of below deck components making for a fast and easy installation.

Innovative Power Options



Long Term Power System
Maintenance-free power for 15 years or more.



Plug-In or Hard-Wire



4 'AA' Batteries

Accessories



8" Cover Plate
EVR-001KJKCP

Available Models

LTPS Power		
Model	Mixing	GPM
EVR-A12D-61ABCPT	Single Supply	0.35
EVR-A12A-61ABCPT	Single Supply	0.5
EVR-A12D-62ABCPT	Mechanical	0.35
EVR-A12A-62ABCPT	Mechanical	0.5
EVR-A12D-63ABCPT	ASSE 1070	0.35
EVR-A12A-63ABCPT	ASSE 1070	0.5

AC Power		
Model	Mixing	GPM
EVR-A12D-41ABCPT	Single Supply	0.35
EVR-A12A-41ABCPT	Single Supply	0.5
EVR-A12D-42ABCPT	Mechanical	0.35
EVR-A12A-42ABCPT	Mechanical	0.5
EVR-A12D-43ABCPT	ASSE 1070	0.35
EVR-A12A-43ABCPT	ASSE 1070	0.5

DC Power		
Model	Mixing	GPM
EVR-A12D-11ABCPT	Single Supply	0.35
EVR-A12A-11ABCPT	Single Supply	0.5
EVR-A12D-12ABCPT	Mechanical	0.35
EVR-A12A-12ABCPT	Mechanical	0.5
EVR-A12D-13ABCPT	ASSE 1070	0.35
EVR-A12A-13ABCPT	ASSE 1070	0.5

Codes & Standards

Certified to ASME A112.18.1 / CSA B125.1 | Certified to NSF/ANSI 61, Section 9
 Certified per ASSE 1070* / ASME A112.1070 / CSA B125.70
 NSF/ANSI 372 Low Lead Content



Complies with ADA requirements as specified in the Americans with Disabilities Act.

*Only models with thermostatic mixer are ASSE 1070 certified.